

we will provide you with faster and more professional value-added services

CODE : 201

80g COATED PAPER/HOT MELT ADHESIVE B-02/WHITE GLASSINE



Application

- Minimum labeling temp: -5℃
 Service temp : -20℃~90℃. (24h after labeling)
- Suitable for Food or Medicine label in conventional glossy.
- Must test to confirm if used in small bottle label (diameter smaller than 30mm).

Print & Process

- Suitable for conventional printing.
- Control the viscosity of print ink, to avoid heavy viscosity cause coating exfoliation.

Shelf life

From date of manufacture:12 months, storage conditions: 23 ± 2 °C & relative humidity 50±5%. Prolonged storage outside these conditions might reduce the shelf life.

Facestock

Coated paper ,glossiness between matte & high gloss.

Indicator	Parameter	Unit	Method
Substance	$80\pm5\%$	g/m^2	I S0536
Caliper	$70\pm5\%$	μm	I S0534

Adhesive

General purpose permanent hot melt adhesive

Liner

Super calendered white glassine

	Indicator	Parameter	Unit	Method
	Substance	$60 \pm 5\%$	g/m²	I S0536
	Caliper	$53\pm5\%$	μm	I S0534
	Tear Resistance	≥300	mN	ISO 1924-2
	Performance	data		
	Indicator	Parameter	Unit	Method
-	Indicator Initial Tack	Parameter ≥17 or PT	Unit N/25mm	Method FTM9, ss
-			N/25mm	
	Initial Tack 90° Peel Adhesion	≥17 or PT ≥9 or PT	N/25mm	FTM9, ss

Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final explanation.