

CODE: 208

80g COATED PAPER/HOT MELT ADHESIVE B-02/WHITE GLASSINE



Application

- Minimum labeling temp: -5℃ Service temp: -20°C~90°C. (24h after labeling)
- Suitable for Food or Medicine label in conventional
- Must test to confirm if used in small bottle label (diameter smaller than 30mm).

Print & Process

- Suitable for conventional printing.
- Control the viscosity of print ink, to avoid heavy viscosity cause coating exfoliation.

Shelf life

From date of manufacture:12 months, storage conditions: 23±2℃ & relative humidity 50 \pm 5%. Prolonged storage outside these conditions might reduce the shelf life.

Facestock

Coated paper, glossiness between matte & high gloss.

Indicator	Parameter	Unit	Method
Substance	80±5%	g/m^2	I S0536
Caliper	$70 \pm 5\%$	μm	I S0534

Adhes i ve

General purpose permanent hot melt adhesive

Liner

Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	60±5%	g/m²	I S0536
Caliper	53±5%	μm	I S0534
Tear Resistance	≥300	mN	ISO 1924-2

Performance data

	Indicator	Parameter	Unit	Method	
	Initial Tack	≥19 or PT	N/25mm	FTM9, ss	
	90° Peel Adhesion (20min)	≥9.5 or PT	N/25mm	FTM2, ss	
	Release forc	ce 10~40	G/25mm	FTM4,ss	
Permanent adhesion 10 H FTM8.ss					

Statement:

• All the statements, tech information &

recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for

its purposes.

We reserve the rights of finally explanation.

FTM8, ss