



# **CODE: 400**

#### Thermal Paper/Hot melt Adhesive B-02/60g White GLassine



## Application

- Minimum labeling temp:-5°C
  Service temp: -20°C~70°C (24h after labeling)
- Suitable for logistics label.
- Suitable for supermarket label.
- Suitable for industrial high speed printing, reduce the abrasion of printer-probe.
- Application environment above 50°C or direct sunlight are not applicable.

## Print & Process

- Suitable for conventional printing.
- Alcohol or volatile organic solvent inks are not applicable.

## Shelf life

From date of manufacture:9 months, storage conditions:  $23\pm2^{\circ}$ C & relative humidity 50±5%. According to the thermal paper properties, please try to avoid keeping the product in high temperature, high humidity, alcohol, oil, plasticizer.

#### **Facestock**

A kind of thermal paper with some water proof, scratch resistance and good print profermance.

Indicator	Parameter	Unit	Method
Substance	$70\pm5\%$	$g/m^2$	ISO 53 <b>6</b>
Caliper	$72\pm5\%$	μm	ISO 534
Optical	1.00		GB/T 28210

## Adhesive

General purpose permanent hot melt adhesive

## Liner

Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	60±5%	g/m²	ISO 536
Caliper	53±5%	μm	ISO 534
Tear Resistance	≥300	mN	ISO 1924-2
Performance	data		

1 or 1 or marros aasa	
Indicator Parameter	Unit Method
Initial Tack ≥14 or PT	N/25mm FTM9, ss
90° Peel Adhesion ≥7 or PT (20min)	N/25mm FTM2, ss
Permanent adhesion 10	H FTM8,ss G/25mm FTM4,ss

## Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final explanation.