



## CODE : 401

Thermal Paper/Hot melt Adhesive B-02/60g Blue GLassine



### Application

- Minimum labeling temp:-5℃  
Service temp: -20℃~70℃ (24h after labeling)
- Suitable for logistics label.
- Suitable for supermarket label.
- Suitable for industrial high speed printing, reduce the abrasion of printer-probe.
- Application environment above 50℃ or direct sunlight are not applicable.

### Print & Process

- Suitable for conventional printing.
- Alcohol or volatile organic solvent inks are not applicable.

### Shelf life

From date of manufacture:9 months, storage conditions: 23±2℃ & relative humidity 50±5%. According to the thermal paper properties, please try to avoid keeping the product in high temperature, high humidity, alcohol, oil, plasticizer.

### Facestock

A kind of thermal paper with some water proof, scratch resistance and good print performance.

Indicator	Parameter	Unit	Method
Substance	70±5%	g/m <sup>2</sup>	ISO 536
Caliper	72±5%	μm	ISO 534
Optical	1.00		GB/T 28210

### Adhesive

General purpose permanent hot melt adhesive

### Liner

Super calendered blue glassine

Indicator	Parameter	Unit	Method
Substance	60±5%	g/m <sup>2</sup>	ISO 536
Caliper	53±5%	μm	ISO 534
Tear Resistance	≥300	mN	ISO 1924-2

### Performance data

Indicator	Parameter	Unit	Method
Initial Tack	≥14 or PT	N/25mm	FTM9, SS
90° Peel Adhesion (20min)	≥7 or PT	N/25mm	FTM2, SS
Permanent adhesion Release force	10 10-40	H G/25mm	FTM8, SS FTM4, SS

### Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final explanation.