

CODE : S050

80g ART PAPER/WATER GLUE PLUS A-01/30μm PET



Application

- Minimum labeling temp: 0°C
Service temp : -20°C~100°C. (24h after labeling);
- Suitable for daily chemical ,food products label in conventional gloss.personal ;
- .Must test to confirm if used small bottle label(diameter smaller than 30mm)

Print & Process

- Suitable for conventional printing
- Pet Liner is suitable for high-speed cross cutting and labeling
- Control the viscosity of print ink, to avoid heavy viscosity cause coating exfoliation.

Shelf life

From date of manufacture:12 months,storage conditions: 23±2°C & relative humidity 50±5%.

Facestock

Art paper ,glossiness between matte & high gloss.

Indicator	Parameter	Unit	Method
Substance	80±5%	g/m ²	ISO 536
Caliper	70±5%	μm	ISO 534

Adhesive

General purpose membrane emulsion acrylic adhesive

Liner

30μm PET

Indicator	Parameter	Unit	Method
Substance	30±5%	g/m ²	ISO536
Haze	≤2.7	%	GB2410-80

Performance data

Indicator	Parameter	Unit	Method
Initial Tack	≥15 or PT	N	FTM9, ss
90° Peel Adhesion (20min)	≥7.5 or PT	N/25mm	FTM2, ss
Shear Min. Release force	3 10-40	hours G/25mm	FTM8 , ss FTM4 , ss

Statement:

- All the statements,tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of finally explanation.

