

**CODE: S10**

**70g COATED PAPER/WATER GLUE A-01/WHITE GLASSINE**



### Application

- Minimum labeling temp: 0°C.  
Service temp : -20°C~100°C. (24h after labeling)
- Suitable for Food or Medicine label in conventional gloss.
- Must test to confirm if used in small bottle label (diameter smaller than 30mm).
- Rough surface substrate is not recommended.

### Print & Process

- Suitable for conventional printing.
- Control the viscosity of print ink, to avoid heavy viscosity cause coating exfoliation.

### Shelf life

From date of manufacture:12 months, storage conditions: 23±2°C & relative humidity 50±5%. Prolonged storage outside these conditions might reduce the shelf life.

### Facestock

Coated paper , glossiness between matte & high gloss.

Indicator	Parameter	Unit	Method
Substance	70±5%	g/m <sup>2</sup>	ISO536
Caliper	61±5%	μm	ISO534

### Adhesive

High-viscosity permanent emulsion acrylic adhesive

### Liner

Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	60±5%	g/m <sup>2</sup>	ISO536
Caliper	53±5%	μm	ISO534
Tear Resistance	≥300	mN	ISO 1924-2

### Performance Data

Indicator	Parameter	Unit	Method
Initial Tack	≥14 or PT	N/25mm	FTM9, ss
90° Peel Adhesion (20min)	≥7 or PT	N/25mm	FTM2, ss
Shear Min. Release force	3 10~40	hours G/25mm	FTM8, ss FTM4, ss

### Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of finally explanation.