



CODE : S206

80 gART PAPER/HOT MELT ADHESIVE B-02/60g YELLOW GLASSINE/B



Application

- Minimum labeling temp:-5°C
Service temp : -20°C~90°C. (24h after labeling)
- Suitable for Food or Medicine label in conventional glossy.
- Must test to confirm if used in small bottle label (diameter smaller than 30mm).

Print & Process

- Suitable for conventional printing.
- Full page printing is not recommend.

Shelf life

From date of manufacture:12 months,storage conditions: 23±2°C & relative humidity 50±5%. Prolonged storage outside these conditions might reduce the shelf life.

Facestock

Art Paper,glossiness between matte & high gloss.

| Indicator | Parameter | Unit | Method |
|-----------|-----------|------------------|--------|
| Substance | 80±5% | g/m ² | ISO536 |
| Caliper | 70±5% | μm | ISO534 |

Adhesive

General purpose permanent hot melt adhesive

Liner

Super calendered yellow glassine

| Indicator | Parameter | Unit | Method |
|-----------------|-----------|------------------|------------|
| Substance | 60±5% | g/m ² | ISO536 |
| Caliper | 53±5% | μm | ISO534 |
| Tear Resistance | ≥300 | mN | ISO 1924-2 |

Performance data

| Indicator | Parameter | Unit | Method |
|----------------------------|--------------|-----------------|------------------------|
| Initial Tack | ≥17 or PT | N/25mm | FTM9, ss |
| 90° Peel Adhesion (20 min) | ≥9 or Pt | N/25mm | FTM2, ss |
| Shear Min. Release force | ≥10 10-40 | hours G/25mm | FTM8 , ss FTM4 , ss |

Statement:

- All the statements,tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final explanation.