

we will provide you with faster and more professional value-added services

CODE: S852 80g ART PAPER/FREEZING ADHESIVE B-05/WHITE GLASSINE



Application

- Minimum labeling temp: -25°C Service temp: -50°C°65°C. (24h after labeling);
- Suitable for food products label in conventional gloss.

 Must test to confirm if used small bottle label(diameter smaller than 30mm)
 - Not suitable for use on PVC surfaces

Print & Process

- With special treatment coated, can be used in letterpress, flexo, gravure and screen printing.
 - Control the viscosity of ink, to avoid heavy viscosity cause coating exfoliation

Shelf life

Facestock

This facestock being corona treated, with excellent softness and tensile properties.

Indicator	Parameter	Unit	Method
Substance	$80 \pm 5\%$	g/m^2	ISO 536
Caliper	$70 \pm 5\%$	μm	ISO 534

Adhesive

Freezing hot melt adhesive

Liner

Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	$60 \pm 5\%$	g/m^2	ISO 536
Caliper	$53 \pm 5\%$	μm	ISO 534
Tear Resistance	≥300	mN	ISO 1924-2

Performance data

Indicator	Parameter	Unit	Method
Initial Tack	≥16 or PT	N	FTM9, ss
90° Peel Adhesion (20min)	8.5or PT	N/25mm	FTM2, ss
ShearMin.	10	hours	FTM8,ss
Release for	ce 10~40	G/25mm	FTM4 .ss

Statement:

- All the statements, tech informat ion & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final ly explanat ion.