

心更快更专业的增值服务于你

# CODE: YA206FC (original code 206(F))

80g Art Paper FSC/Hot melt adhesive/ Yellow Glassine FSC



#### Application

## Fulfill the requirement of ROHS, REACH

- Minimum labeling temp: -5°C
  Service temp: -20°C~70°C (24h after labeling)
- Suitable for food labels, medicine labels in conventional gloss.
- Must test to confirm if used in small bottle label (diameter smaller than 30mm).

## **Print & Process**

- Suitable for conventional printing.
- The facestock can be beautifully printed and colors of patterns are full.
- For fine barcode printing, comprehensive print test is required.

# Shelf life

From date of manufacture: 12 months Storage conditions: 23±2°C & relative humidity 50±5%.

Prolonged storage outside these conditions might reduce the shelf life.

# Facestock

FSC Art paper, glossiness between matte & high gloss.

Indicator	Parameter	Unit	Method
Substance	$80\pm5\%$	$g/m^2$	ISO 536
Caliper	$70\pm5\%$	μm	ISO 534

## Adhesive

General purpose permanent hot melt adhesives

This adhesive complies with FDA section 21 (175.105) and can be used for not-contact labeling of food, pharmaceutical and cosmetic products.

## Liner

Super calendered FSC yellow glassine

Indicator	Parameter	Unit	Method
Substance	$58\pm5\%$	$g/m^2$	ISO 536
Caliper	$51\pm5\%$	μm	ISO 534
Tear Resistance	≥300	mN	GB/T 455

## **Performance data**

Indicator	Parameter	Unit	Method
Initial Tack	$\geq 17 \text{ or } PT$	Ν	FTM9, ss
90°Peel Adhesion (20min)	≥9 or PT	N/25mm	FTM2, ss
Shear Strength	≥10	hours	FTM8, ss

#### Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products sold should be tested by the customer in the end-use environment to confirm compliance with the requirements of that environment and to determine which materials to purchase.
- We reserve the rights of final explanation.