

心更快更专业的增值服务于你

# **CODE: YT424** (original code 424)

Thermal Paper/Hot melt adhesive/ 50g White Glassine



# Application

Fulfill the requirement of ROHS, REACH, BPA FREE

- Minimum labeling temp: -5°C
  Service temp: -20°C~70°C (24h after labeling)
- Suitable for logistics labels.
- Suitable for supermarket labels.
- Suitable for industrial high-speed printing with minimal wear on printing probes.
- Long term exposure to environments above 50 °C or direct sunlight is not recommended.

# Print & Process

- Suitable for conventional printing.
- Not suitable for inks containing alcohol or volatile organic solvents.

# Shelf life

From date of manufacture: 9 months

Storage conditions:  $23\pm2^{\circ}$ C & relative humidity  $50\pm5\%$ . According to the characteristics of thermal paper, please try to avoid exposing the product to high temperature, high humidity, alcohol, oil, plasticizer, etc.

# Facestock

Thermal paper with water resistance, scratch resistance and good printing performance.

Indicator	Parameter	Unit Method	
Substance	$70\pm5\%$	$g/m^2$	ISO 536
Caliper	$72 \pm 5\%$	μm	ISO 534
Anti Plasticizer	≥60	%	40°C, 24h
Optical	≥1.00		GB/T 28210

#### Adhesive

General purpose permanent hot melt adhesive

This adhesive complies with FDA section 21 (175.105) and can be used for not-contact labeling of food, pharmaceutical and cosmetic products.

#### Liner

#### Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	$50\pm5\%$	$g/m^2$	ISO 536
Caliper	$43 \pm 5\%$	μm	ISO 534
Tear resistance	≥300	mN	GB/T 455

# **Performance Data**

Indicator	Parameter	Unit	Method
Initial Tack	$\geq 14 \text{ or } PT$	Ν	FTM9, ss
90° Peel Adhesion (20min)	$\geq 7 \text{ or } PT$	N/25mm	FTM2, ss
Shear Strength	≥10	Н	FTM8, ss

#### Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products sold should be tested by the customer in the end-use environment to confirm compliance with the requirements of that environment and to determine which materials to purchase.
- We reserve the rights of final explanation.