

# CODE: YT430 (original code 430)

Direct Thermal Paper/Hot melt adhesive/ White Glassine



## Application

Fulfill the requirement of ROHS, REACH, BPA FREE

- Minimum labeling temp: -5°C
  Service temp: -20°C~65°C (24h after labeling)
- Suitable for supermarket retail info labels, barcode printing labels.
- Not suitable for environment above 50°C direct sunlight.
- PVC substrate is not suitable.
- Not suitable for applications with alcohol exposure.
- Long-term high humidity is not recommended.

## Print & Process

- Suitable for conventional printing.
- Alcohol or volatile organic solvent inks are not applicable.

## Shelf life

From date of manufacture: 9 months

Storage conditions: 23±2°C & relative humidity 50±5%. According to the properties of thermal paper, please try to avoid keeping the product in high temperature, high humidity, alcohol, oil, plasticizer.

## Facestock

A kind of thermal paper with a certain degree of water resistance and good performance at printing.

Indicator	Parameter	Unit	Method
Substance	70±5%	$g/m^2$	ISO 536
Caliper	72±5%	μm	ISO 534
Optical	≥1.00		GB/T 28210

### Adhesive

General purpose permanent hot melt adhesive

This adhesive complies with FDA section 21 (175.105) and can be used for not-contact labeling of food, pharmaceutical and cosmetic products.

#### Liner

### Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	58±5%	g/m²	ISO 536
Caliper	51±5%	μm	ISO 534
Tear resistance	≥300	mN	GB/T 455

## **Performance data**

Indicator	Parameter	Unit	Method
Initial Tack	$\geq 14 \text{ or } PT$	Ν	FTM9, ss
90°Peel Adhesion (20min)	$\geq$ 7 or PT	N/25mm	FTM2, ss
Shear Strength	≥10	Н	FTM8, ss

#### Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final explanation.