

Code: YTT965 (original code S965)

70g Thermal Transfer Paper/Hot melt adhesive/
White Glassine



Application

Fulfill the requirement of ROHS, REACH

- Minimum labeling temp: -5°C
Service temp: -20°C~70°C (24h after labeling)
- Suitable for food labels, blank ribbon labels in conventional glossy, etc.
- Can be used on small bottles with diameter less than 30mm. Recommended to sample test before mass print.

Print & Process

- Suitable for conventional printing.
- Full page printing is not recommended.
- Conventional ribbon printing has excellent performance. Must to test the applicability of the material and carbon ribbon first.

Shelf life

From date of manufacture: 12 months

Storage conditions: 23±2°C & relative humidity 50±5%.

Prolonged storage outside these conditions might reduce the shelf life.

Facestock

The Facestock has been super calendered, with smoothly surface.

Indicator	Parameter	Unit	Method
Substance	70±5%	g/m ²	ISO 536
Caliper	70±3	μm	ISO 534
Whiteness	≥80	%	ISO 2470

Adhesive

General purpose permanent hot melt adhesive

This adhesive complies with FDA section 21 (175.105) and can be used for not-contact labeling of food, pharmaceutical and cosmetic products.

Liner

Super calendered white glassine

Indicator	Parameter	Unit	Method
Substance	58±5%	g/m ²	ISO 536
Caliper	51±5%	μm	ISO 534
Tear Resistance	≥300	mN	GB/T 455

Performance data

Indicator	Parameter	Unit	Method
Initial Tack	≥ 17 or PT	N	FTM9, ss
90° Peel Adhesion (20min)	≥9 or PT	N/25mm	FTM2, ss
Shear Min	≥10	hours	FTM8, ss

Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
- We reserve the rights of final explanation.