

**CODE: YW907** (original code 907)

**70g Woodfree paper/Acrylic adhesive / Blue Glassine**



### Application

Fulfill the requirement of ROHS, REACH, VOC

- Minimum labeling temp: +5°C  
Service temp: -20°C~80°C (24h after labeling)
- Suitable for a variety of low-gloss labels, price tags, etc.
- Rough surface substrate is not recommended.

### Print & Process

- Suitable for normal color printing and inkjet printing.
- The facestock can be beautifully printed and colors of patterns are full.

### Shelf life

From date of manufacture: 12 months  
Storage conditions: 23±2°C & relative humidity 50±5%.  
Prolonged storage outside these conditions might reduce the shelf life.

### Facestock

Woodfree paper with fine ink-absorbency.

Indicator	Parameter	Unit	Method
Substance	70±5%	g/m <sup>2</sup>	ISO 536
Caliper	85±5%	μm	ISO 534

### Adhesive

High viscosity permanent acrylic emulsion adhesive

This adhesive complies with FDA section 21 (175.105) and can be used for not-contact labeling of food, pharmaceutical and cosmetic products.

### Liner

Super calendered blue glassine

Indicator	Parameter	Unit	Method
Substance	58±5%	g/m <sup>2</sup>	ISO 536
Caliper	51±5%	μm	ISO 534
Tear Resistance	≥300	mN	GB/T 455

### Performance data

Indicator	Parameter	Unit	Method
Initial Tack	≥14 or PT	N	FTM9, ss
90°Peel Adhesion (20min)	≥7 or PT	N/25mm	FTM2, ss
Shear Strength	≥3	hours	FTM8, ss

### Statement:

- All the statements, tech information & recommendations are based on the tests believed to be reliable but do not constitute a guarantee or warranty. All products sold should be tested by the customer in the end-use environment to confirm compliance with the requirements of that environment and to determine which materials to purchase.
- We reserve the rights of final explanation.